

# PRL GLASS SYSTEMS

## Ladder Pull

Product Data Sheet

MADE IN THE USA



### 1. PRODUCT NAME:

Ladder Pull

### 2. MANUFACTURER:

PRL Glass systems manufactures the ladder pull system as described on this sheet.

### LIMITATIONS:

Ladder Pull system is only limited by the materials from which it is fabricated.

Ladder Pull should be assembled using the components listed:

### LP ASSEMBLY:

- (1) 1-1/4" Diameter stainless steel exterior handle
- (1) 1-1/4" Diameter stainless steel interior handle

- (4) Type 316 SS cup point socket set screw 1/4"-20 thread, 3/16" Length
- (1) Type 304 Stainless steel shoulder bolt 5/16"-18 thread 1.4" length. (Length will vary with door thickness)

- (1) retainer metal washer
- (1) shoulder bolt metal washer

### FINISHES:

Standard circular # 4 brushed or polished #8 finishes are available for stainless steel

### MATERIAL:

304 stainless steel alloy

### GLASS HOLE REQUIRED:

5/8" Diameter

### 3. INSTALLATION:

The Ladder Pull must be attached to surfaces that are approved or selected by the manufacturer and shall be detailed on all shop drawings

### 4. MAINTENANCE:

The Ladder Pull surface can be kept clean by the use of ordinary soaps and mild cleansers.

Abrasive cleaners should not be used

