

End User Manual

To ensure optimal performance, long service life, and safety, please follow the guidelines below for the proper operation, maintenance, and cleaning of your door system.

Operation

Smooth Opening and Closing:

Always operate the door gently. Avoid slamming the door, as this can damage hinges, seals, or hardware.

Check that the door latches completely and that the handle returns to its neutral position after use.

Adjustments:

If the door becomes misaligned or difficult to operate, contact a qualified installer to adjust the hinges using the built-in vertical adjustment feature (up to 1/4").

Do not attempt to force the door or modify hardware components yourself.

Safety:

Keep hands and fingers clear of hinges and closing edges.

Ensure children are supervised when operating the door.

Maintenance

Performing routine maintenance will extend the life of your SunnyDoor system and preserve its performance:

Every 3–6 Months:

Inspect hinges and fasteners; tighten if necessary.

Check weather seals for proper placement and wear.

Verify that the door opens and closes smoothly.

Every 6–12 Months:

Lubricate hinges and moving parts with a light machine oil or manufacturer-approved lubricant.


Inspect the frame for structural integrity and check for gaps or shifting.

Replace any worn or damaged weather seals to maintain airtightness.

Annually:

Confirm that the frame remains plumb, level, and square.

Schedule a professional inspection if the door shows excessive wear, misalignment, or unusual noise.

 **Important:** Failure to follow recommended maintenance may result in premature wear, compromised performance, or voided warranty.

Regular cleaning preserves the appearance and performance of the door:

cleaning

Frame & Door Surface:

Clean aluminum profiles with mild soap and water using a soft cloth.

Avoid abrasive cleaners, solvents, or scouring pads that may scratch the finish.

Glass Panels:

Use a non-abrasive glass cleaner and a microfiber cloth to remove dirt and smudges.

Do not use ammonia-based products that could damage sealants or coatings.

Weather Seals:

Wipe with a damp cloth to remove dust and debris.

Avoid petroleum-based products, which may degrade the seals.



FOR SERVICE ISSUES CONTACT DOOR INSTALLER

NAME:

TEL:

FOR FURTHER DETAILS AND ADVICE PLEASE VISIT

<https://prlglass.com>